

GTR-2-AS / Adjustable Speed Tube Rocker

• Accommodates tubes from 0.5mL to 10mL (50mL with

optional insert)



If a double platform is more

than you need, ask about the Globe

Scientific GTR-AS single tier tube rocker.

GTR-2-AS / Adjustable Speed

10 30

Radial dial for simple speed adjustment from 0 to 30rpm







Tube Rocker

Specifications	GTR-AS
Working Area (each tier)	190.5mm W x 127mm D (7.5in W x 5in D)
Maximum Load	1kg / (2.2lbs)
Maximum Tilt Angle	30°
Voltage	100-240VAC, 50-60Hz
Power	15W
Speed	0-30rpm adjustable speed
Dimensions (WxDxH)	295×160×165mm/(11.6 x 6.3 x 6.5in)
Weight	2kg / (4.4lbs)
Operating Temperature	5-50°C
Permissible Relative Humidity	80%RH (non-condensing)
Warranty	2 Years

ORDERING INFORMATION

Item#	Description	Unit
GTR-2-AS	Double Tier Tube Rocker, Adjustable Speed, 0-30rpm, 100-240VAC, 50-60Hz	Each
GTR-AS-10X5-10ML	10-Position Silicone Insert for 5-10mL specimen collection tubes, for GTR-AS and GTR-2-AS	Each
GTR-AS-4X50ML	4-Position Silicone Insert, for 50mL centrifuge tubes, for GTR-AS and GTR-2-AS	Each

GTR-AS-10X5-10ML

Replacement inserts for 5-10mL and 50mL tubes are available

GTR-AS-4X50ML

www.globescientific.com

Customer Service, Sales and Technical Support:

Phone 1 (800) 394-4562 • 1 (201) 599-1400

Fax 1 (201) 599-1406 E-mail mail@globescientific.com

© 2024 Globe Scientific. All rights reserved.

The Globe Scientific logo is a registered trademark of Globe Scientific.